



# STATICWORX ESD BOLT BASICS

Bolt Basics offers many ergonomic features and options that make the chairs adaptable to most end users and their required applications. They have become a standard in many Fortune 1000 companies.



## Specifications

Seat:	19"W x 18" D, contoured seat with 2 1/2" thick high resilient foam (A)
Back:	17 1/2"W x 12 1/2" H fully upholstered standard back, 2 1/2" high resilient foam (A)
Upholstery:	Conductive fabric or vinyl
Control:	Autonomous Tilt - 3 levers - Seat height, seat angle, back angle. Back height adjusted with knob. (AT)
Footring:	20" diameter, adjustable chrome (R20) (for bench heights only)
Base:	5-legged aluminum base, polished (A28P) or black powder coated (A28B)
Casters:	2" hard dual wheel caster, black hooded (O2) or chrome hooded (O1)
Wt Cap:	300 lbs.

## Options:

### Seat Height Ranges:

- Model 1721- approx 17" to 21 1/2" (desk ht)
- Model 1925- approx 19" to 25 1/2" (low bench ht)
- Model 2229 - approx 22" to 29 1/2" (med bench ht)
- Model 2535 - approx 25" to 35" (high bench ht)

- Control: Back Tilt (BT), Independent Tilt (IT)
- Back: High back - 16"H (B)  
Extra high back - 20"H (C)
- Seat: Waterfall seat pan -19"W x 18"D (B)  
Short contour seat pan -19"W x 16 1/2"D (C)  
Short waterfall seat pan - 19"W x 16 1/2"D (D)
- Arms: Adjustable, fixed and rotating
- Armpads: Upholstered and polyurethane
- Upholstery: Selection of fabrics and vinyls
- Base: 5-legged nylon base
- Casters: Selection of casters and glides

ESD Package (E)  
ANSI/ESD S20.20 Compliant  
Tested per ANSI/ESD 12.1 - 2019

